



CINQUE

The CINQUE is Wineemotion's 5 bottle model and the best in its class, combining quality, design, elegance, and silent functioning in a space- saving and compact design. This model is suggested for small installations and is perfect for commercial business and residential use. The Dual Zone model for 2 Whites and 3 Reds is widely requested for country clubs and lounges.

PRODUCT FEATURES

★ Available Model

- ▶ **Ambient temperature** 5 bottles (no refrigeration - no front glass panel)
- ▶ **Refrigerated** 5 bottles (42-70°F)
- ▶ **Dual Zone** 5 bottles, 2 White (42-58°F) + 3 Red ("fixed" cellar temperature, approx. 60-62°F)

★ Usage Configuration

- ▶ Behind the bar use
- ▶ Customer use

★ System Control

- ▶ Key card activation

★ Servings

- ▶ Three pour adjustable portion control: taste, ½ glass, full glass

★ Preservation

- ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)

★ Gas System

- ▶ External gas system

★ Display

- ▶ Individual bottle position 16-character LCD displays for general info and card balance

★ Lighting

- ▶ Ambient LED system that uses static light

★ Bottle Lifting System

- ▶ Powered by pneumatic pistons assisted by mechanical springs
- ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake

★ ISOL-Plus Technology

- ▶ Patented unique valve that prevents aromatic cross-contamination of wines in the same unit

★ OSHA Requirements

- ▶ ELT certified for safety
- ▶ ETL sanitation

★ Optional Customizations

- ▶ Customizable serigraphic design/color/logo on display board
- ▶ Customizable external finish – RAL color in gloss or matte finish

Refrigerated Models Only (with removable front plexiglass panel)

★ Positioning

- ▶ Dispenser clearance requires 6 inches from the top

★ Condensation Drainage

- ▶ Not required—dispenser uses an internal evaporator

★ Cooling System

- ▶ Chilled by gas compressor powered by Hitachi

★ Compressor Positioning

- ▶ Compressor is located in the back

Software Activated Systems Only

★ Modules Interfacing

- ▶ Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol

★ Dynamic Lighting / RGB Color Lighting

- ▶ Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
CINQUE (Ambient Temperature)	26.65 in.	25 in.	13.83 in.	99 lbs..	50-60 Hz	90-260VAC 60 Watt
CINQUE (Refrigerated/ Dual Zone)	26.65 in.	25 in.	13.83 in.	119 lbs..	50-60 Hz	90-260VAC 110 Watt