



otto

The OTTO is Wineemotion's 8 bottle model in the Series 3 collection. With the front "removable" plexiglass panel, the OTTO is the best system to go with for customer use. Perfect for commercial use on a large scale, the OTTO is the ideal model for installations needing two or more machines. With its sleek, modern Italian style, and outstanding display, the OTTO can enhance any bar, restaurant, or wine store.

PRODUCT FEATURES

- ★ **Available Model**
 - ▶ **Ambient temperature** 8 bottles (no refrigeration - no front glass panel)
 - ▶ **Refrigerated** 8 bottles (42-70°F)
- ★ **Usage Configuration**
 - ▶ Behind the bar
 - ▶ Customer use
- ★ **System Control**
 - ▶ Key card activation
- ★ **Servings**
 - ▶ Three pour adjustable portion control: taste, ½ glass, full glass
- ★ **Preservation**
 - ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)
- ★ **Gas System**
 - ▶ External gas tank
- ★ **Display**
 - ▶ Individual bottle position 16-character LCD for general info and card balance
- ★ **Lighting**
 - ▶ Ambient LED system that uses static light
- ★ **Bottle Lifting System**
 - ▶ Powered by pneumatic pistons which are assisted by mechanical springs
 - ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake

- ★ **ISOL-Plus Technology**
 - ▶ Patented unique valve which prevents aromatic cross-contamination of wines in the same unit
- ★ **OSHA Requirements**
 - ▶ ELT certified for safety
 - ▶ ETL sanitation
- ★ **Optional Customizations**
 - ▶ Customizable serigraphic design/color/logo on display board
 - ▶ Customizable external finish – RAL color in gloss or matte finish

Refrigerated Models Only (with removable front plexiglass panel)

- ★ **Positioning**
 - ▶ Dispenser clearance requires 6 inches from the top
- ★ **Condensation Drainage**
 - ▶ Not required—dispenser uses an internal evaporator
- ★ **Cooling System**
 - ▶ Chilled by gas compressor powered by Hitachi
- ★ **Compressor Positioning**
 - ▶ Compressor is located in the back

Software Activated Systems Only

- ★ **Modules Interfacing**
 - ▶ Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol
- ★ **Dynamic Lighting / RGB Color Lighting**
 - ▶ Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
OTTO (Ambient Temperature)	39.44 in.	25 in.	13.83 in.	143 lbs.	50-60 Hz	90-260VAC 75 Watt
OTTO (Refrigerated/ Dual Zone)	39.44 in.	25 in.	13.83 in.	167 lbs.	50-60 Hz	90-260VAC 250 Watt



OTTO PLUS

The OTTO PLUS is Wineemotion's 8 bottle model in the Series 3 collection *with double glass doors*, is the best way to go for behind the bar installations. Perfect for commercial use on a large scale, the OTTO PLUS is the ideal model for installations needing two or more machines. With its sleek, modern Italian style, the OTTO PLUS can enhance any bar, restaurant, or wine store.

PRODUCT FEATURES

- ★ **Available Model**
 - ▶ **Ambient temperature** 8 bottles (no refrigeration - no front glass panel)
 - ▶ **Refrigerated** 8 bottles (42-70°F)
- ★ **Usage Configuration**
 - ▶ Behind the bar
 - ▶ Customer use
- ★ **System Control**
 - ▶ Key card activation
- ★ **Servings**
 - ▶ Three pour adjustable portion control: taste, ½ glass, full glass
- ★ **Preservation**
 - ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)
- ★ **Gas System**
 - ▶ External gas tank
- ★ **Display**
 - ▶ Individual bottle position 16-character LCD for general info and card balance
- ★ **Lighting**
 - ▶ Ambient LED system that uses static light
- ★ **Bottle Lifting System**
 - ▶ Powered by pneumatic pistons which are assisted by mechanical springs
 - ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake

- ★ **ISOL-Plus Technology**
 - ▶ Patented unique valve which prevents aromatic cross-contamination of wines in the same unit
- ★ **OSHA Requirements**
 - ▶ ELT certified for safety
 - ▶ ETL sanitation
- ★ **Optional Customizations**
 - ▶ Customizable serigraphic design/color/logo on display board
 - ▶ Customizable external finish – RAL color in gloss or matte finish

Refrigerated Models Only (with removable front plexiglass panel)

- ★ **Positioning**
 - ▶ Dispenser clearance requires 6 inches from the top
- ★ **Condensation Drainage**
 - ▶ Not required—dispenser uses an internal evaporator
- ★ **Cooling System**
 - ▶ Chilled by gas compressor powered by Hitachi
- ★ **Compressor Positioning**
 - ▶ Compressor is located in the back

Software Activated Systems Only

- ★ **Modules Interfacing**
 - ▶ Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol
- ★ **Dynamic Lighting / RGB Color Lighting**
 - ▶ Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
OTTO PLUS (Refrigerated/ Dual Zone)	39.44 in.	25 in.	13.83 in.	167 lbs.	50-60 Hz	90-260VAC 250 Watt