



quattro

The QUATTRO Series 2 is Wineemotion's entry-level, 4 bottle system, and is the 1st model in the Series 2 line. Developed for any type of situation, it is perfect for behind-the-bar use and for residential use. It was created to be user friendly and low maintenance, with industrial grade reliability and 2-years warranty.

PRODUCT FEATURES

★ **Available Model**

- ▶ **Ambient** 4 bottles (no refrigeration, no glass door panel)
- ▶ **Refrigerated** 4 bottles (44 - 78°F)
- ▶ **Dual Zone** 4 bottles, 2 White (44-70°F) + 2 Red ("fixed" cellar temp, approx. 58-60°F)

★ **Usage Configuration**

- ▶ Behind the bar use
- ▶ Residential use

★ **System Control**

- ▶ Activation code

★ **Servings**

- ▶ Three pour adjustable portion control: taste, ½ glass, full glass

★ **Preservation**

- ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)

★ **Gas System**

- ▶ External gas tank

★ **Display**

- ▶ Single 16-character LCD display for general info

★ **Lighting**

- ▶ Ambient LED system that uses static light

★ **Bottle Lifting System**

- ▶ Manual spring loaded pistons
- ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake

★ **ISOL-Plus Technology**

- ▶ Patented unique valve that prevents aromatic cross-contamination of wines in the same unit

★ **OSHA Requirements**

- ▶ ETL certified for safety
- ▶ ETL sanitation

**Refrigerated Models Only
(with glass door)**

★ **Positioning**

- ▶ Dispenser clearance requires 6 inches from the top

★ **Condensation Drainage**

- ▶ Not required—dispenser uses an internal evaporator

★ **Cooling System**

- ▶ Chilled by gas compressor powered by Hitachi

★ **Compressor Positioning**

- ▶ Compressor is located in the back

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
QUATTRO (Ambient Temperature)	21.6 in.	22.6 in.	12.6 in.	83 lbs.	50-60 Hz	90-260VAC 40 Watt
QUATTRO (Refrigerated/ Dual Zone)	21.6 in.	22.6 in.	12.6 in.	99 lbs.	50-60 Hz	90-260VAC 110 Watt