

QUATTRO+4



The QUATTRO+4 is Wineemotion's 8 bottle system with unparalleled technology that utilizes two temperature-controlled chambers with a beautiful *front "removable" plexiglass panel* that is the best solution to display the bottle. It is our most versatile model for accommodating the desired number of white or red wines at different temperatures. The QUTTRO+4 is elegantly designed and built to handle the rigors of a commercial setting. It is built to enhance any wine program, increase profits, and reduce waste. This is the most popular model for behind-the-bar uses.

PRODUCT FEATURES

- ★ **Available Model**
 - ▶ **Dual Temperature Zone:** 8 bottles, 4 White (42-58°F)+ 4Red (59-70°F)
 - ▶ **Dual Temperature Zone (Special Version):** 8 bottles, 4+4 with adjustable 3 White + 5 Red
 - ★ **Usage Configuration**
 - ▶ Behind the bar
 - ▶ Customer use
 - ★ **System Control**
 - ▶ Key card activation
 - ★ **Servings**
 - ▶ Three pour adjustable portion control: taste, ½ glass, full glass
 - ★ **Preservation**
 - ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)
 - ★ **Gas System**
 - ▶ External gas tank
 - ★ **Display**
 - ▶ Individual bottle position 16-character LCD for general info and card balance
 - ★ **Lighting**
 - ▶ Ambient LED system that uses static light
 - ★ **Bottle Lifting System**
 - ▶ Powered by pneumatic pistons which are assisted by mechanical springs
 - ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake
 - ★ **ISOL-Plus Technology**
 - ▶ Patented unique valve which prevents aromatic cross-contamination of wines in the same unit
 - ★ **OSHA Requirements**
 - ▶ ELT certified for safety
 - ▶ ETL sanitation
 - ★ **Optional Customizations**
 - ▶ Customizable serigraphic design/color/logo on display board
 - ▶ Customizable external finish – RAL color in gloss or matte finish
-
- Refrigerated Models Only**
(with removable front plexiglass panel)
- ★ **Positioning**
 - ▶ Dispenser clearance requires 6 inches from the top
 - ★ **Condensation Drainage**
 - ▶ Not required—dispenser uses an internal evaporator
 - ★ **Cooling System**
 - ▶ Chilled by gas compressor powered by Hitachi
 - ★ **Compressor Positioning**
 - ▶ Compressor is located in the back
-
- Software Activated Systems Only**
- ★ **Modules Interfacing**
 - ▶ Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol
 - ★ **Dynamic Lighting / RGB Color Lighting**
 - ▶ Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
QUATTRO (Refrigerated/ Dual Zone)	39.44 in.	25 in.	13.83 in.	167 lbs.	50-60 Hz	90-260VAC 250 Watt



QUATTRO+4 PLUS

The QUATTRO+4 PLUS utilizes two temperature-controlled chambers with beautiful double glass doors that makes it the best solution for behind-the-bar use. It's elegant and adjustable design can accommodate the desired number of red or white wine bottles being stored, making it our most flexible model for any commercial setting. The QUATTRO+4 PLUS is built to enhance any wine program, increase profits, and reduce waste.

PRODUCT FEATURES

★ Available Model

- ▶ **Dual Temperature Zone:** 8 bottles, 4 White (42-58°F)+ 4 Red (59-70°F)
- ▶ **Dual Temperature Zone (Special Version):** 8 bottles, 4+4 with adjustable 3 White + 5 Red

★ Usage Configuration

- ▶ Behind the bar
- ▶ Customer use

★ System Control

- ▶ Key card activation

★ Servings

- ▶ Three pour adjustable portion control: taste, ½ glass, full glass

★ Preservation

- ▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)

★ Gas System

- ▶ External gas tank

★ Display

- ▶ Individual bottle position 16-character LCD for general info and card balance

★ Lighting

- ▶ Ambient LED system that uses static light

★ Bottle Lifting System

- ▶ Powered by pneumatic pistons which are assisted by mechanical springs
- ▶ No limitations on bottle size: 375mL/750mL/1000mL/Sake

★ ISOL-Plus Technology

- ▶ Patented unique valve which prevents aromatic cross-contamination of wines in the same unit

★ OSHA Requirements

- ▶ ELT certified for safety
- ▶ ETL sanitation

★ Optional Customizations

- ▶ Customizable serigraphic design/color/logo on display board
- ▶ Customizable external finish – RAL color in gloss or matte finish

Refrigerated Models Only (with removable front plexiglass panel)

★ Positioning

- ▶ Dispenser clearance requires 6 inches from the top

★ Condensation Drainage

- ▶ Not required—dispenser uses an internal evaporator

★ Cooling System

- ▶ Chilled by gas compressor powered by Hitachi

★ Compressor Positioning

- ▶ Compressor is located in the back

Software Activated Systems Only

★ Modules Interfacing

- ▶ Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol

★ Dynamic Lighting / RGB Color Lighting

- ▶ Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Electrical Requirements
QUATTRO (Refrigerated/ Dual Zone)	39.44 in.	25 in.	13.83 in.	167 lbs.	50-60 Hz	90-260VAC 250 Watt