







The SEI is Wineemotion's 6 bottle model for offering wine by the glass. Its <u>double glass doors</u> and sturdy construction makes the SEI perfect for any commercial setting. Owning a Wineemotion SEI will enhance your wine sales and communicate to your customers the caliber of your wine program. As with all Wineemotion systems, the SEI can be customized to match or elevate any décor and vision.

## **PRODUCT FEATURES**

#### \* Available Model

- ▶ **Refrigerated** 6 bottles (42-70°F)
- ► Dual Temperature Zone 6 bottles, 3 White (42-58°F) + 3 Red (59-78°F)

#### ★ Usage Configuration

- Behind the bar
- Customer use

## **★** System Control

Key card activation

## Servings

► Three pour adjustable portion control: taste, ½ glass, full glass

## **★** Preservation

▶ 30-day wine preservation with argon gas or food grade nitrogen (99.9% pure)

## **★** Gas System

External gas tank

## Display

Individual bottle position 16-character
LCD for general info and card balance

#### ◆ Lighting

Ambient LED system that uses static light

## ★ Bottle Lifting System

- Powered by pneumatic pistons which are assisted by mechanical springs
- No limitations on bottle size: 375mL/750mL/1000mL/Sake

## ★ ISOL-Plus Technology

 Patented unique valve which prevents aromatic cross-contamination of wines in the same unit

#### OSHA Requirements

- ▶ ELT certified for safety
- ▶ ETL sanitation

#### **★** Optional Customizations

- Customizable serigraphic design/color/logo on display board
- Customizable external finish RAL color in gloss or matte finish

# All Refrigerated Models (with double glass doors)

## Positioning

▶ Dispenser clearance requires 6 inches from the top

## Condensation Drainage

▶ Not required—dispenser uses an internal evaporator

## **★** Cooling System

▶ Chilled by gas compressor powered by Hitachi

## **★** Compressor Positioning

▶ Compressor is located in the back

## **Software Activated Systems Only**

## **★** Modules Interfacing

 Can be used with LAN network (recommended) or Wi-Fi with TCP/IP protocol

## Dynamic Lighting / RGB Color Lighting

 Optional RGB Colored light tones can be adjusted to match ambient lighting

Models	Width	Height	Depth	Weight	Frequency	Requirements	
SEI (Ambient Temperature)	30.67 in.	24.9 in.	13.83 in.	150 lbs.	50-60 Hz	90-260VAC 110 Watt	
SEI (Refrigerated/ Dual Zone)	30.67 in.	24.9 in.	13.83 in.	150 lbs.	50-60 Hz	90-260VAC 250 Watt	